

Application / Specification Data for Tungsten ToolWorks' Series Drills

Drilling speeds & feeds are expressed in decimal inches and based on hole depth of up to 3X diameter. For deeper hole ratios reduce speeds and feeds by 10% to 25%. Tungsten ToolWorks® drills feature diameter tolerances 40% tighter than industry standards. Plus, all shanks are SFR (shrink-fit ready). Try our drills with SmoothCoat for a superb leap in lubricity, productivity, and tool life.

Material	SFPM	SFPM	1/16"	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	5/8"	3/4"
Steel	Uncoated	SmoothCoat	Feed Rate: Inches Per Rev (IPR)									
1018 / 1020	100 to 250	100 to 300	.0010	.0030	.0050	.0070	.0090	.0100	.0110	.0120	.0140	.0160
4140 / 4340 / P20	60 to 230	60 to 260	.0010	.0030	.0050	.0070	.0090	.0100	.0110	.0120	.0140	.0160
Stainless Steel												
303 / 304 / 316	60 to 150	60 to 200	.0010	.0030	.0050	.0060	.0070	.0080	.0090	.0100	.0120	.0140
410 / 420 / 440C	40 to 100	40 to 150	.0010	.0030	.0050	.0060	.0070	.0080	.0090	.0100	.0120	.0140
15-5/17-4 ≤ 32HRc	75 to 175	75 to 200	.0010	.0015	.0025	.0040	.0050	.0060	.0070	.0080	.0090	.0100
15-5/17-4 ≥ 32HRc	50 to 125	50 to 150	.0005	.0010	.0015	.0025	.0030	.0035	.0038	.0040	.0050	.0060
13-8 / 316L	60 to 150	60 to 200	.0010	.0030	.0050	.0060	.0070	.0080	.0090	.0100	.0120	.0140
Tool Steel												
A2/D2/H13 ≤ 32HRc	60 to 150	60 to 200	.0010	.0015	.0025	.0040	.0050	.0060	.0070	.0080	.0090	.0100
A2/D2/H13 ≥ 32HRc	40 to 100	40 to 150	.0005	.0010	.0015	.0025	.0028	.0030	.0035	.0040	.0050	.0060
Titanium												
6Al-4V	40 to 150	40 to 175	.0005	.0010	.0020	.0025	.0028	.0030	.0035	.0040	.0050	.0060
High Temp Alloys												
Inconel 625	30 to 70	30 to 80	.0010	.0015	.0025	.0040	.0050	.0060	.0070	.0080	.0090	.0100
Inconel 718	30 to 45	30 to 50	.0005	.0010	.0020	.0025	.0028	.0030	.0035	.0040	.0050	.0060
Cast Iron												
Gray Iron ≤ 32HRc	150 to 300	150 to 350	.0010	.0030	.0050	.0070	.0085	.0100	.0110	.0120	.0140	.0160
Ductile Iron	150 to 300	150 to 350	.0010	.0030	.0050	.0070	.0085	.0100	.0110	.0120	.0140	.0160
Non-Ferrous												
6061 T6 Aluminum	250 to 750	250 to 1000	.0010	.0030	.0050	.0070	.0085	.0100	.0110	.0120	.0140	.0160
Copper, Brass, Bronze	150 to 400	150 to 500	.0010	.0030	.0050	.0070	.0085	.0100	.0110	.0120	.0140	.0160
Plastic	250 to 1000	250 to 1000	.0010	.0030	.0050	.0070	.0085	.0100	.0110	.0120	.0140	.0160

Drill Specifications:

Cutting Diameter	+0.000/-0.003
Shank Diameter	+0.000/-0.003
Point Angle	± 1%
LOC	+0.060/-0.090
OAL	±.120



Metric Cutting Diameter	+0.000/-0.008mm
Metric Shank Diameter	+0.000/-0.008mm
Metric Radius	±1%
Metric LOC	+1.5/-2.2mm
Metric OAL	±3.0mm

**TUNGSTEN
TOOLWORKS**.COM